



PREMIUM CLUTCHED TUBING SWIVEL

The Premium Clutched Tubing Swivel allows left or right hand set tension anchors to be set. Pulling tension will allow the Premium Clutched Swivel to freely rotate in either direction. When the tension anchor needs to be unset, weight is put back on the swivel and the clutch is engaged allowing left or right hand torque to be applied for unsetting.

Tubing Swivel Size		Maximum OD		Minimum ID		Total Length	
inch	mm	inch	mm	inch	mm	inch	mm
2 7/8"	73.0	4.20"	106.7	2.441"	62.0	21"	533.4
3 1/2"	88.9	5.00"	127.0	2.992"	76.0	21"	533.4

Patent Pending

*Premium ALS is pleased to offer other connection sizes and types

Both the Premium "Downhole Resettable" Clutched Tubing Swivel and Premium Clutched Tubing Swivel are easily redressed with the appropriate redress kits.

PREMIUM "DOWNHOLE RESETTABLE" CLUTCHED TUBING SWIVEL

The Premium "Downhole Resettable" Clutched Tubing Swivel allows the user to set left or right hand set tension anchors, disengage the clutch and rotate freely under tension. If the tubing string needs to be moved, the swivel can be easily re-set downhole, allowing the tension anchor to be unset and the tubing can be moved freely. When in position, the tension anchor can be re-set and the swivel can be disengaged again for free rotation. This unique feature will result in considerable savings in rig time and reduce the production down time by eliminating the need to trip the tubing to re-set the swivel at surface.

Tubing Swivel Size		Maximum OD		Minimum ID		Total Length	
inch	mm	inch	mm	inch	mm	inch	mm
2 7/8"	73.0	4.20"	106.7	2.441"	62.0	27.0"	685.8
3 1/2"	88.9	5.000"	127.0	2.992"	76.0	27.0"	685.8

Patent Pending

*Premium ALS is pleased to offer other connection sizes and types